

Specifications

Provide a Fiberglass Reinforced Composite (FRC) Ground set flagpole Model # 30X as manufactured by PLP Composites, Fitzwilliam, NH 03447.

The flagpole shall have a mounting height of 30' and 3' below grade for an overall length of 33'.

The butt diameter shall be 6.75" and the top diameter 3". The pole weight shall be approximately 77 lbs. and a total shipping weight of 151 lbs.

The flagpole shall be manufactured of fiberglass woven roving and polyester resin with 75% of the reinforcing fibers oriented in the axial plane for maximum stiffness and 25% in the radial plane for required hoop strength. Load calculations shall be based on AASHTO and NAAMM standards with the pole designed with a two to one (2:1) safety factor for 125 mph winds, unflagged, with a 1.3 gust factor.

The flagpole shall have an Entasis taper and shall be void of vertical mold seams.

The flagpole shall be sanded smooth and coated with a high gloss Aliphatic Polyurea coating system which provides extended UV protection and weatherability.

Standard colors include: White, Black, Bronze, Faux-Luminum, & Metallic Bronze



Aeolus Series - Model #30X	Standard Fittings:		Project:
30' Above Grade Height	6" Gold Anodized Ball	60' of #10 Polyester Halyard	
33' Overall Height	Cast FG Stationary Truck	16" Flash Collar	Location:
Top Diameter - 3"	1 pair of Brass Snaps	8.5" Nylon Cleat	
Butt Diameter - 6.75"	1 pair of vinyl covers	3'x8" Ground Sleeve	Date:

PLP Composites

57 Creamery Road - PO Box 429, Fitzwilliam, NH 03447 - Phone: 800-262-6075 - www.plpcomp.com or www.zeusflagpoles.com - info@plpcomp.com